

GLORIA®**6/9/12 kg****PH 6 / PH 9 / P 6 / P 12 EASY**

portable

cartridge operated

powder



GLORIA PH 6 EASY

GLORIA EASY line - multi-purpose powder cartridge-operated fire extinguishers

GLORIA Powder PH/P EASY extinguishers - extremely robust and multi-purpose powder fire extinguishers.

Immediate, fast extinguishing due to the effect of cooling and suppression, enriched with an anti-catalytic effect.

GLORIA PH 6 / PH 9 / P 6 / P 12 EASY – cartridge operated, handy fire extinguishers for A, B and C fire classes

Operation with an in-house developed, fibre-glass reinforced, high-quality special plastic valve in the distinctive GLORIA design, which is resistant to tension, chemicals, moisture as well as corrosion.

GLORIA EASY line powder extinguishers may be used in the following fire classes:

Type	A	B	C	D	MED
PH 6 EASY	43	233	•	—	—
PH 9 EASY	55	233	•	—	⊗
P 6 EASY	34	183	•	—	⊗
P 12 EASY	55	233	•	—	⊗

Areas of use:

- Outdoor areas
- Chemist's laboratories
- Cars
- Underground parking and car parks
- Heating systems
- Industries
- Marine industry

Service-friendly - large filler opening, fast and easy exchange of cartridge.

Easy operable squeeze-grip operation.

Environmentally friendly, performance-differentiated high-quality ABC extinguishing powder of variable capacity.

Reignition in the case of fires of solids is suppressed.

GLORIA extinguishing powders are hydrophobic and non-toxic.

Serially equipped with quality wall bracket with two rubber grommets, appropriate car brackets are available.

With colour-coding of extinguishing agent - gray for powder.



- Pull the **metal safety pin A**.
- By shortly pressing down the **lever B** for the first time, the **puncture pin C** laps the **CO₂ gas cartridge D**.
- At the same time CO₂ abruptly flows through the **blow pipe E** into the container and ensures a good swirling of the powder.
- By pressing down the **lever B** again, the powder gets through the **driptube F** into the **hose assembly G**.
- By releasing the **lever B** the extinguishing stream is being disconnected.



Product and performance features

- Fire extinguisher container made from quality steel with two suspension clips, externally coated with polyester resin powder coating (free from heavy metals) for a long life-time.
- Consistent, high-strength fibre-glass reinforced special plastic valve body.
- Black-coloured, anodised metal union nut.
- Consistent neck ring M 74.
- Internal CO₂-gas cartridge with PE-coating and connection thread M 18.
- Three bolts welded on the bottom of the container ensure excellent fixing of the footing against drop-off or twisting.
- Long-lasting hose assembly with fabric lining made from synthetical rubber material.
- Robust, shock-resistant plastic footing with nozzle adapter allowing for stability and protection against damages and corrosion.
- Approved to use at electrical installations up to 1000 V at min. distance of 1 m.
- Each fire extinguisher delivered in a separate cardboard box.



Type	Model	PN	Weight of charge unit [kg]	Extinguishing agent	Qty of extinguishing agent [kg]	Propellant gas	Discharge time [s]	Throw [m]	Working temperature [°C]	Bracket H/W/D Ø [mm]
PH 6 EASY	PG 6 H	802171.3015	≈10,1	ABC-Powder	6	CO ₂	18	6	-30 / +60	550 / 280 / 165, 150
PH 9 EASY	PG 9 H	802181.0000	≈15	ABC-Powder	9	CO ₂	20	7	-30 / +60	595 / 300 / 165, 170
P 6 EASY	PG 6 H	802171.0000	≈10,1	ABC-Powder	6	CO ₂	18	6	-30 / +60	550 / 280 / 165, 150
P 12 EASY	PG 12 H	802191.0000	≈19	ABC-Powder	12	CO ₂	23	7	-30 / +60	640 / 310 / 205, 190

GLORIA PH 6 / PH 9 / P 6 / P 12 EASY - technical data

subject to technical changes

