

GLORIA®**6 kg****stored pressure****PDE 6****portable****Product and performance features**

- Pull the **metal safety pin A**.
- With pressing the **lever B** the **valve C** opens.
- Extinguishing agent enters the **driptube D** from where it goes to the **hose E** then to the **nozzle F** and spray.



GLORIA PDE 6 - valve look



GLORIA PDE 6 - valve look



GLORIA PDE 6 - footing

- Fire extinguisher container made from high quality steel, covered outside with weather-resistant, environmentally friendly (heavy-metal-free) 100% polyester resin coating.
- Unified, robust and proven valve body made of aluminium - all valve components with standardized screw connection.
- Constant visual inspection of the pressure thanks to the pressure gauge and check valve.
- Single internal thread M 30.
- Uniform, standardized spare parts.
- Proven, impact resistant plastic footing with nozzle holder - stability and protection of the device against damage and corrosion.
- Durable hose with textile fabric insert made of synthetic rubber material.
- Approved to use on electrical installations up to 1000 V at minimum distance 1 m.
- Important fire protection information visible at a glance on well-arranged silkscreen.
- Each extinguisher delivered in individual carton box.



Type	Model	PN	Weight of charge unit [kg]	Extinguishing agent	Qty of extinguishing agent [kg]	Propellant gas	Discharge time [s]	Throw [m]	Working temperature [°C]	Bracket H/W/D, Ø [mm]
PDE 6 w/o footing*	PGE 6 L	802111.2290	≈9,4	ABC Powder	6	nitrogen	≈22	≈6	-30 / +60	607 / 280 / 160, 150

GLORIA PDE 6 - technical data, *also available version with footing.

subject to technical changes

UTC CCS MANUFACTURING POLSKA SP. Z O.O.
KOLEJOWA 24, 39-100 ROPCZYCE
POLAND

PHONE +48 17 22 10 206
FAX +48 17 22 10 241
pfx@fs.utc.com



**United
Technologies**

Climate | Controls | Security

GLORIA®**6 kg****PDE 6**

portable

stored pressure

powder



**Simple,
Universal,
Good!**

PROTEX
Feuerlöscher
6 kg ABC-Pulver
B

1. Sicherungsstift herausziehen
 2. Schlauch fassen
 3. Taste niederdrücken
- A B C

Vorsicht bei elektrischen Anlagen.
Nur bis 1000 V; Mindestabstand 1 m.

Nach jeder Benutzung neu lagern!
Halter freigeben oder 2 Jahre ab 1. Druckverlustzeit überlassen.
Nur wenn Löscher / Halter und / oder Halter reparieren,
die mit dem entsprechenden Muster übereinstimmen.

Nettoinhalt: 6 kg (13,23 lb) Funktionsbereich: -20°C bis +40°C
Druck: 13 bar (Sicherheit) Nr. d. Anzeigerstellung: 1P 42/93 089 04 2
3rd 20°C Typ: 708 9

GLORIA GmbH
D-59321 Waderloh - Tel. +49 (0) 23 21 777-0

GLORIA PDE 6

GLORIA PDE 6 - practical device with high extinguishing efficiency

Easy activation with a lever - both for carrying and extinguishing.

Ergonomic design allows instant usage upon pulling the safety pin.

Squeeze-grip operation allows simple and effective extinguishing.

GLORIA PDE 6 – stored pressure extinguisher with practical hand lever fitting

Universal standard equipment for a wide range of applications.

GLORIA fire extinguishers PDE 6 can be used in the following fire classes:

Type	A	B	C	MED
PDE 6	34	183	•	⚙️

Areas of use:

- Outdoor areas
- Pharmacy labs
- Chemical industry
- Vehicles, freight forwarders
- Garages, car parks
- Heating systems
- Workshops
- Warehouses
- Shipping companies
- Police, Fire Department, Border Guard

Squeeze-grip mechanism - when speed and easiness of operation are key features (especially in stress situations).

Equipped with hanging bracket, quality wall holder in standard. Compatible vehicle holders available optionally.

Environmentally friendly, performance-differentiated quality ABC extinguishing powder.

Extinguishing stream surpressible - at any time.

Serviceable and refillable after use - for many times.