

GLORIA®**6/9l****SDPF 6 / SDPF 9**

portable

stored pressure

foam

GLORIA SDPF 9

GLORIA SDPF series - stored pressure frost-proof extinguishers

Easy activation with a lever- both for carrying and extinguishing.

Ergonomic design allows instant usage upon pulling safety pin.

High quality product version with uniform hand lever, fitted with black anodized valve body and pressure relief valve. Versatile application, approved for use from -20 °C.

GLORIA SDPF 6 / SDPF 9 – foam fire extinguisher with practical hand lever fitting.

Frost-proof equipment for a wide range of applications.

GLORIA foam fire extinguishers SDPF 6 / 9 can be used in the following fire classes:

Type	A	B	C	MED
SDPF 6	21	183	—	—
SDPF 9	27	233	—	—

Areas of use:

- Offices and Living rooms
- Schools
- Hospitals
- Airports
- Industries with flammable liquids
- Department stores, storage areas
- Administrative and manufacturing areas
- Workshops
- Shipping companies
- Restaurants
- Hotels

Foam extinguishers are practical in petrochemistry as well as in public spaces. Contrary to powder, they do not cause a „dust cloud“ effect which may impede breathing and sight. An indisputable advantage is the easiness to clean afterwards.

Comes with quality wall bracket with two rubber grommets. Car holder and footing available on request.

Device ready for use at any time!

Three bolts welded to the bottom of the container ensure excellent fitting of the footing against falling or twisting.

SDPF 6 / SDPF 9

portable



- Pull the **metal safety pin A**.
- Pressing the **lever B** opens the **valve C**.
- Extinguishing agent enters the **driptube D** from where it goes to the **hose E** then to the **nozzle F** and spray.



GLORIA SDPF 6 - valve lock



GLORIA SDPF series - footing and nozzle



GLORIA SDPF 6 - metal safety pin

Product and performance features

- Fire extinguisher container made from high quality steel, covered outside with weather-resistant, environmentally friendly (heavy-metal-free), 100% polyester resin coating.
- Cylinder with high quality internal lining prevents from corrosion and assures long life time of extinguisher.
- Extinguisher with standard M 50 thread and PRV.
- Guaranteed frost-proof extinguishing agent.
- Robust, impact resistant plastic footing with hose nozzle holder ensures stability and protection of the device against damage and corrosion.
- Durable hose with fabric insert made of synthetic rubber material LABS (Linear Alkyl Benzene Sulfonate) free.
- Approved to use on electrical installations up to 1000 V at minimum distance 1 m.
- Legible marking of extinguisher according to standard EN 3-7 with a permanent screen printing technique.
- Each fire extinguisher delivered in a separate cardboard box.



Type	Model	PN	Weight of charge unit [kg]	Extinguishing agent	Q-ty of extinguishing agent [l]	Propellant gas	Discharge time [s]	Throw [m]	Working temperature [°C]	Bracket H/W/D, Ø [mm]
SDPF 6	SD6DLWB	803681.2950	≈10,2	AB Foam, film-forming	6	nitrogen	40	4	-20 / +60	540 / 295 / 182, 170
SDPF 9	SD9DLWB	801741.2950	≈15,8	AB Foam, film-forming	9	nitrogen	50	4	-20 / +60	617 / 300 / 202, 190

GLORIA SDPF 6 / SDPF 9 - technical data
subject to technical changes

