

GLO-001 / GLO-002 / GLO-003 / GLO-004 / GLO-005

accessories

Show the way
to safety
in case of
fire!



GLORIA GLO-008 emergency lighting fixture.

GLORIA GLO-001

GLORIA GLO-002

GLORIA GLO-004

GLORIA GLO-005

Emergency and escape sign lights provide security and prevent accidents during evacuation.

GLORIA products meet the prescribed standards and are also diverse in design and installation options.

Areas of use:

- Schools,
- Movie theaters,
- Department stores,
- Restaurants and restaurants,
- Hotels.

Continuous or standby circuit.

Emergency light bridging time of 3 hours.

Illuminant LED white.

Pictogram set included (screen printing RAL 6032).

Test button:

Test results, Status display (operation, fault) via colored LED, Automatic charge monitoring, Deep discharge protection with reclosing lock, Idle and short circuit shutdown of the inverter.

GLO-001: single-battery signage, slim, convex plastic luminaire for universal mounting (wall / ceiling / cantilever).

GLO-002: single-battery signage, slim

plastic luminaire for universal mounting (wall / ceiling / cantilever) with additional light emission downwards.

GLO-003: single-battery signage, Innovative plastic LED panel light for universal mounting (wall / ceiling / cantilever).

GLO-004: low-cost single-battery escape-sign light, classic ceiling-mounted plastic luminaire with two-sided lettering or for use as escape route luminaire.

GLO-005: single battery escape sign light as a design variant, stainless steel LED design ceiling light.

Type	PN	Casing material	Dimensions [mm] (W x H x D)	Distance [m]	Power consumption [W]	Temperature range [°C]	Battery type	Voltage range	Protection class / type
GLO-001	925991.0001	plastic	250 x 174 x 34	24	2	-5 / +40	4.8 V / 0.5 Ah	230V 50/60Hz, 220V DC +25/-20%	II / IP54
GLO-002	925991.0002	plastic	260 x 155 x 70	24	2	-5 / +40	4.8 V / 2.0 Ah	230V 50/60Hz, 220V DC +25/-20%	I / IP54
GLO-003	925991.0003	plastic	250 x 178 x 34	22	2	-5 / +40	4.8 V / 0.5 Ah	230V 50/60Hz, 220V DC +25/-20%	II / IP54
GLO-004	925991.0004	plastic	360 x 92 x 125	16	1.5	-5 / +40	4.8 V / 2.0 Ah	230V 50/60Hz, 220V DC +25/-20%	II / IP54
GLO-005	925991.0005	stainless steel	236 x 181 x 64	24	3	-5 / +40	4.8 V / 0.5 Ah	230V 50/60Hz, 220V DC +25/-20%	I / IP40

GLORIA Emergency Lighting Fixtures - technical data.

subject to technical changes