



- Pull the **yellow safety pin A**.
- By lifting the **handle B**, the **puncture pin C** laps the **CO₂ gas cartridge D**.
- Abruptly **CO₂** flows through the **blowpipe E** into the container and ensures a good swirling of powder.
- Through the **driptube F** powder gets into the **hose assembly G**.
- The rotating and suppressible **extinguishing pistol H** allows for a targeted and largescale fire fighting.



Product and performance features

- Fire extinguisher container made from quality steel with two suspension clips, externally covered with polyester resin powder coating (free from heavy metals) for a long life-time.
- Consistent, high-strength fibre-glass reinforced special plastic valve body with ergonomic, trend-setting operating elements.
- Consistent neck ring M 74, with black-coloured, anodised metal union nut.
- Internal CO₂ cartridge with PE-coating and consistent connection thread M 18.
- Three bolts welded on the bottom of the container ensure excellent fixing of the footing against drop-off or twisting.
- Long-lasting hose assembly with fabric lining made from synthetical rubber material.
- Robust, shock-resistant plastic footing with nozzle adapter allowing for stability and protection against damages and corrosion.
- Approved to use at electrical installations up to 1000 V with minimum distance of 1 m.
- Each fire extinguisher delivered in a separate cardboard box.
- Possibility of certification of other devices for compliance with the MED Directive.



Type	Model	PN	Weight of charge unit [kg]	Extinguishing agent	Qty of extinguishing agent [kg]	Propellant gas	Discharge time [s]	Throw [m]	Working temperature [°C]	Bracket H/W/D Ø [mm]
PX 6 STAR	PG 6 H	800631.3016	≈9,9	ABC-Powder	6	CO ₂	24	6	-30 / +60	500 / 300 / 165, 150
PH 6 STAR	PG 6 H	800631.3015	≈9,9	ABC-Powder	6	CO ₂	24	6	-30 / +60	500 / 300 / 165, 150
PH 9 STAR	PG 9 H	800641.0000	≈14,3	ABC-Powder	9	CO ₂	23	7	-30 / +60	555 / 290 / 185, 170
P 6 STAR	PG 6 H	800631.0000	≈9,9	ABC-Powder	6	CO ₂	24	6	-30 / +60	500 / 300 / 165, 150
P 12 STAR	PG 12 H	800651.0000	≈18,7	ABC-Powder	12	CO ₂	32	7	-30 / +60	600 / 290 / 205, 190

GLORIA PX 6 / PH 6 / PH 9 / P 6 / P 12 STAR - technical data
subject to technical changes



GLORIA®**6/9/12 kg****PX 6 / PH 6 / PH 9 / P 6 / P 12 STAR**

portable

cartridge operated

powder



The
innovative
semi-automatic!
Unlock, Lift,
Ready!

GLORIA

Feuerlöscher

6 kg ABC-Pulver
B

- 1 Sicherungslasche abziehen
- 2 Gerät am Handgriff anheben
- 3 Löschpistole betätigen



vorsicht bei elektrischen Anlagen.
Nur bis 1000 V; Mindestabstand 1 m.

Nach jeder Benutzung neu füllen!
Überprüfungsintervalle alle 2 Jahre auf Einstufungsbeschriftung überprüfen.
Nur solche Löschmittel verwenden und einsetzen, die mit dem anerkannten Muster übereinstimmen.
Löschmittel: Pulver
Nettoinhalt: 6 kg
Druckbereich: -30° C bis +60° C
Typ

GLORIA GmbH
D-59929 Wadersloh
Tel. 0 20 28 77 4037 Fax 77 150
www.gloria.de

GLORIA PH 6 STAR

GLORIA STAR line - the royal league - innovative fire extinguisher with maximum performance!

The innovative and compact appearance of fittings is characteristic for GLORIA's unique style. This series is marked by performance, cost-efficiency and design which form a post-modern symbiosis.

Immediate, fast extinguishing due to the cooling and suppression, enriched with an anti-catalytic effect.

GLORIA PX 6 / PH 6 / PH 9 / P 6 / P 12 STAR – designed for intuitive use, for A, B and C fire classes

A comprehensive product range with trend-setting, consistent, semi-automatic operation, with an in-house developed, fibre-glass reinforced, high-quality special plastic valve in the distinctive GLORIA design, integrated with stable handle.

GLORIA PX 6 / PH 6 / PH 9 / P 6 / P 12 STAR extinguishers may be used in extinguishing following fire classes:

Type	A	B	C	MED
PX 6 STAR	55	233	•	⚙️
PH 6 STAR	43	233	•	—
PH 9 STAR	55	233	•	—
P 6 STAR	34	233	•	⚙️
P 12 STAR	55	233	•	—

Areas of use:

- Outdoor areas
- Chemist's laboratories
- Cars
- Underground parking and car parks
- Heating systems
- Industries
- Marine industry

Service-friendly - large filler opening.

Intuitive and thus applicable extraordinary fast: Unlock - Lift handle - Ready!

Environmentally friendly, performance-differentiated high-quality ABC extinguishing powders of variable firefighting capacity.

Reignition in the case of fires of solids is suppressed.

GLORIA extinguishing powders are hydrophobic and non-toxic.

Serially equipped with quality wall bracket with two rubber grommets, appropriate car bracket is available separately.