



NEW FROM SOLAX Triple Power 3.0



Triple Power 3.0 Battery

Features

- Systematic design, in-depth optimization and seamless connection with Solax Hybrid inverter
- Unique battery heating technology, which is capable to work at low temperature^[1]
- Safest type of LiFePO₄ battery, an adoption of high-performance processors
- Modular stacking design, easy installation, supporting floor and wall mounting
- Auto power replenishment technology is adopted to prevent battery over-discharge
- IP65, supporting indoor and outdoor installation
- Remote fault diagnosis, upgrade and maintenance
- Multiple communication interfaces: RS485, CAN
- International brand devices, better stability
- Long life cycle, more than 6000 times
- Safety Cert. TUV, CE, UN38.3 and so on

[1] With Hybrid G4 inverter

info@solaxpower.com
service@solaxpower.com



For more information, please contact us

www.solaxpower.com
AU: +61 1300 476529
DE: +49 6142 4091664

Global: +86 571-56260008
UK: +44 2476 586998
NL: +31 (0) 852 737932

Triple Power 3.0

MC0600*→

HV10230*→



	T-BAT-SYS-HV-3.0	T-BAT-SYS-HV-6.0	T-BAT-SYS-HV-9.0	T-BAT-SYS-HV-12.0
Nominal voltage [V]	102.4	204.8	307.2	409.6
Operating voltage range [V]	90~116	180~232	270~348	360~464
Total energy [kWh]	3.0	6.1	9.2	12.2
Usable energy ^[1] [kWh]	2.7	5.5	8.3	10.9
Rated capacity [Ah]	30			
Nominal power [kW]	2.5	5.1	7.6	10.2
Max. power [kW]	3.0	6.1	9.2	12.2
Recommend charge/discharge current [A]	25			
Max. charge/discharge current [A]	30			
Battery roundtrip efficiency	95%			
Cycle life [90% DOD]	6000 Cycles			
Expected life time / Warranty [year]	10			
Available charge/discharge temperature range [°C]	-30 to 50			
Storage temperature [°C]	-20 to 50 (3 months)			
Relative humidity [%]	0~100			
Altitude [m]	Below 3000			
Degree of protection	IP65			
Battery to Inverter	RS485/CAN2.0			
Battery to battery/BMS	CAN2.0			
Master control capacity indicator	4LED (25%, 50%, 75%, 100%)			
Master control LED indicator (Working mode)	1 LED			
System switch (on/off)	ButtonX1+BreakerX1			
Certificate	CE/IEC62619/UN38.3/IEC62040/UKCA			
Hazardous materials classification	Class 9			
Dimensions(WxHxD) [mm]	MC0600: 482.5x173.5x153 HV10230: 482.5x471.5x153			
Net weight [kg]	MC0600: 7.5kg +HV10230: 34.5kg	MC0600: 7.5kg +2xHV10230: 69kg	MC0600: 7.5kg +3xHV10230: 103.5kg	MC0600: 7.5kg +4xHV10230: 138kg

[1] Test conditions: 90% DOD, 0.2C charger & discharger @+25°C

* MC0600: Master Box (one MC0600 can be connected 1~4 HV10230)

* HV10230: Slave Battery Pack

* Max charge/discharge current may be variant with different inverter models

V2.0. Information may be subject to modify without notice.

650.00011.00